



## FEED SCREWS IN STOCK

### Feed Screws:

SIZE	MAKE	Mat'l	MODEL	OAL	PRICE
25mm	ARBURG	CPM 420V	320S-500-150	34.594"	1000/ea
30mm	ARBURG	USED 1.174	320C-500-250	38.438"	500/ea
30mm	ARBURG	COL/CHROME	270M-350-90	28.622"	1000/ea
35mm	ARBURG	USED 1.368	305-210-700	27.559	350/ea
25mm	BATTENFELD	CRU-WEAR	125	34.567"	750/ea
25mm	BATTENFELD	USED .977	500	41.141	250/ea
35mm	BATTENFELD	USED 1.370	315	47.000	500/ea
40mm	BATTENFELD	CRU-WEAR	315	46.772"	1250/ea
40mm	BATTENFELD	COL/CHROME	BA750/300	44.125	500/ea
45mm	BATTENFELD	CPM 420V	315	46.563"	1500/ea
<del>45mm</del>	<del>BATTENFELD</del>	<del>USED 1.763</del>	<del>500</del>	<del>52.312"</del>	<del>750/ea.</del>
32mm	BOY	OEM	15-S	25.813"	350/ea
18mm	CINCI VISTA	Nit 135M	Sentry	27.125"	500/ea
20mm	CINCI VISTA	OEM Used	OD: .784	23.375	250/ea
22mm	CINCI VISTA	CPM 9V	CLEARSTAR	37.625	750/ea
35mm	CINCI VISTA	COL/CHROME	VT220 DS	59.438"	500/ea
35mm	CINCI VISTA	COL/CHROME	VT220 DS	53.229"	500/ea
1.31	CINCINNATI	CPM 9-V	T 75-4	36.500"	1000/ea
1.62	CINCINNATI	COL/CHROME	150T-8	44.750"	350/ea
<del>80mm</del>	<del>CINCI VISTA</del>	<del>COL/CHROME</del>	<del>VH440-54</del>	<del>81.250"</del>	<del>2500/ea</del>

~~OD measures: 3.142/3.141 (OEM spec) Has Dual-Wave barrier & mixer (sells new for over \$4500.00)~~

80mm CINCI VISTA COL/CHROME VH440-54 81.250" 1000/ea

OD measures: 3.141/3.135 Has mattox mixer & ball check

SIZE	MAKE	Mat'l	MODEL	OAL	PRICE
2 ½	DAVIS STD	COL/CHROME	XA244310J	76.250"	750/ea
USED: 2.491 OD					

30mm	ENGEL	NEW OEM	Liq. Sil	20.563	150/ea
------	-------	---------	----------	--------	--------

<del>35mm</del>	<del>ENGEL</del>	<del>NEW CPM 9V</del>	<del>330 Inj</del>	<del>42.992"</del>	<del>1500/ea</del>
-----------------	------------------	-----------------------	--------------------	--------------------	--------------------

40mm	ENGEL	USED: 1.763	D-2	40.563"	250/ea
------	-------	-------------	-----	---------	--------

45mm	ENGEL	D-2: 1.763	ES80/100	36.438"	500/ea
------	-------	------------	----------	---------	--------

45mm	ENGEL	USED: 1.761	8 SPLINE	50.420"	350/ea
------	-------	-------------	----------	---------	--------

45mm	ENGEL	USED: 1.764	CPM 9-V	50.420"	500/ea
------	-------	-------------	---------	---------	--------

STA threads loose

60mm	ENGEL	USED: 2.349	DBG FLT	65.125"	350/ea
------	-------	-------------	---------	---------	--------

2"	HPM	New Cru-Wear		54.625"	1000/ea
----	-----	--------------	--	---------	---------

2"	HPM	Used: 1.994	Dual-Wave	54.625"	750/ea
----	-----	-------------	-----------	---------	--------

2"	HPM	Used: 1.987	CAM MIXER	54.625"	250/ea
----	-----	-------------	-----------	---------	--------

2"	HPM	Used: 1.994	Dual-Wave	44.812"	750/ea
----	-----	-------------	-----------	---------	--------

2 ½"	HPM	New Cru-Wear	tool stl	66.625"	1750/ea
------	-----	--------------	----------	---------	---------

51mm	JSW	Used: 1.992	CPM 9V	47.375"	750/ea
------	-----	-------------	--------	---------	--------

58mm	JSW	Used: 2.275	OEM	54.527"	1500/ea
------	-----	-------------	-----	---------	---------

2"	JOMAR	Used: 1.994	Mixing	74.281"	500/ea
----	-------	-------------	--------	---------	--------

<del>30mm</del>	<del>KAWAGUCHI</del>	<del>NEW, CPM 9-V</del>		<del>33.188"</del>	<del>1000/ea</del>
-----------------	----------------------	-------------------------	--	--------------------	--------------------

36mm	KAWAGUCHI	CPM 9V, Fits	K80-I	40.125"	1250/ea
------	-----------	--------------	-------	---------	---------

42mm	KAWAGUCHI	Used, CPM	9-V	45.625"	500/ea
------	-----------	-----------	-----	---------	--------

<del>50mm</del>	<del>KAWAGUCHI</del>	<del>NEW, CPM 9-V</del>		<del>50.625"</del>	<del>1000/ea</del>
-----------------	----------------------	-------------------------	--	--------------------	--------------------

~~KS200B TR26 thd~~

50mm	KAWAGUCHI	NEW, 4140/CHROME		44.250"	1000/ea
------	-----------	------------------	--	---------	---------

JEKS 180 Tr30 thd

42mm	KLOCKNER	Used, 1.653"	OD	45.938"	250/ea
------	----------	--------------	----	---------	--------

2"	Reed TG	Used, .015"	useable	48.500	150/ea
----	---------	-------------	---------	--------	--------

2 ½"	REED TD	NEW, STELLITE/CHROME		50.000"	1500/ea
------	---------	----------------------	--	---------	---------

2 ½"	REED TD	Used, Downsized	Spcl	59.688	500/ea
------	---------	-----------------	------	--------	--------

SIZE	MAKE	Mat'l	MODEL	OAL	PRICE
20mm	ROBOSHOT	CPM 420V	OD: .785/4	20.236"	350/ea
<del>26mm</del>	<del>ROBOSHOT</del>	<del>USED 1.017</del>	<del>110I-48C</del>	<del>25.875</del>	<del>150/ea</del>
32mm	ROBOSHOT	Carbide	165R-113	35.236"	750/ea
32mm	ROBOSHOT	Rebuilt	165R-113	35.236"	250/ea
44mm	ROBOSHOT	Used 1.706	250R-252	44.688	100/ea
1 ¼"	STOKES	USED: Chrome/Rebuilt		29 ¼"	150/ea
1 ¼"	STOKES	USED: CPM 420-V		29 ¼"	350/EA
1 ¼"	STOKES	USED: OEM		29 ¼"	150/EA
1.62	STOKES	USED: CPM 9-V		36.750	500/ea
		Like New: 1.621" OD			
36mm	TOSHIBA	NEW: ISF 2B CPM 420V		40.787	1250/ea
		(OD: 1.412/1.411)			
36mm	TOSHIBA	USED: ISF/G 5Y		46.500	1000/ea
		(OEM DBG OD: 1.410/1.409)			
50mm	TOSHIBA	REBUILT, ISG 10A, OEM		57.875"	1500/ea
55mm	TOSHIBA	NEW: ISC/E 225 9B		57.875"	1200/ea
		CPM 9-V Tool Steel			
60mm	TOSHIBA	USED: worn 2.318" OD		67.205"	250/ea
		STA installed			
70mm	TOSHIBA	USED: 4140/Col/Chrome		83.937"	1000/ea
		OEM DBG flight in very good condition			
		Flights measure: 2.745/2.744			
70mm	TOSHIBA	USED: EMERGENCY ONLY		74.625"	350/ea
		Flights: 2.690 in trans/Galling			
<del>105mm</del>	<del>TOSHIBA</del>	<del>New, ISG 59B 4140,</del>		<del>105.125"</del>	<del>2500/ea</del>
		<del>Colmanoy#56/Chrome Has Dual barrier</del>			
		<del>Flighted section with PULSAR mixer</del>			
36mm	TOYO	USED: OEM Screw		37.323"	500/ea
1 ¾"	TRUEBLOOD	NEW, Nitralloy, Nit.		33.875"	500/ea
25mm	VAN DORN	NEW, CRU-WEAR Tool		31.125"	750/ea
DEMAG		Steel HT to 58/60 Rc			
30mm	VAN DORN	NEW, Nitralloy, Nit.		33.187"	350/ea
		30/40 4R-330D			
35mm	VAN DORN	NEW, CRU-WEAR Tool		40.550"	1250/ea
DEMAG		Steel HT to 58/60 Rc			
		(Fits ET 80 & 50-200C Rotating Ram)			

40mm VAN DORN DEMAG	NEW, CRU-WEAR Tool Steel HT to 58/60 Rc (Fits ET 120 Rotating Ram)	45.032"	1500/ea
50mm VAN DORN	USED: OK	1.964" OD 49.625"	250/ea
75mm VAN DORN	USED: CORE FOR REBULD	72.500"	75/ea
80mm VAN DORN	USED LIKE-NEW FOR PVC OD measures to OEM spec.	75.767"	1000/ea